

# RE200 AC750 Wi-Fi Range Extender

Stable Dual Band Wi-Fi Extension



RE200










# Highlights

## Extend the Range of Your Wi-Fi Network

The AC750 Wi-Fi Range Extender connects to your router wirelessly, strengthening and expanding its signal into areas it can't reach on its own, achieving speeds of 300Mbps on the 2.4GHz band and 433Mbps on the 5GHz band.



## Perfect Location at a Glimpse

An Intelligent Signal light helps you quickly find the best location to install the range extender.



TP-Link AC750 Wi-Fi Range Extender RE200

## **Features**







#### Ease of Use

- Intuitive Web UI Ensures quick and simple installation without
- Fast Encryption One-touch WPA wireless security encryption with the WPS button
- Hassle-free Management with Tether App Network management is made easy with the TP-Link Tether App, available on any Android or iOS device
- $\label{lem:continuous} \textbf{Online Upgrade} \text{Keeps you informed of the latest firmware and allows onling updating on the web UI}$

#### Speed

- Ultimate Wireless Speed Combined wireless speeds of up to 300Mbps (over 2.4GHz) and 433Mbps (over 5GHz)
- Support 802.11 ac Provides a data transfer rate 3 times faster than 802.11n for each stream
- MIPS 24KEc CPU A 575/580 MHz MIPS 24K™ CPU core makes multi-tasking easy and boosts data transfer rate

#### Reliability

- Simultaneous Dual Band Separate Wi-Fi bands enable more devices to connect to your network without a drop in performance
- Reliable Connection Three Internal antennas for optimal Wi-Fi coverage and reliable wireless connections

# **Specifications**

#### Hardware

- Ethernet Port: 1 10/100Mbps RJ45 Port
- · Button: WPS Button, Reset Button
- · Antenna: 3 Internal Antennas
- · Power Consumption: 6.5W
- · Dimensions (L × W × H): 110×65.8×75.2mm





For more information, please visit

http://www.to-link.com/en/products/details/RE200.html or scan the QR code left

#### Wireless

- Wireless Standards: IEEE 802.11a/n/ac 5GHz, IEEE 802.11b/g/n 2.4GHz
- Frequency: 2.4GHz and 5GHz
- Signal Rate: 300Mbps at 2.4GHz, 433Mbps at 5GHz
- Transmit Power: <20dBm
- Reception Sensitivity:

5GHz:

11a 6Mbps: -94dBm, 11a 54Mbps: -79dBm 11ac HT20 MCS0: -94dBm, 11ac HT20 MCS8: -73dBm 11ac HT40 MCS0: -91dBm, 11ac HT40 MCS9: -67dBm 11ac HT80 MCS0: -88dBm, 11ac HT80 MCS9: -64dBm

11g 54Mbps: -81dBm, 11n HT20 MCS7: -79dBm 11n HT40 MCS7: -76dBm

- Wireless Function: Enable/Disable Wireless Radio,
- Wireless Security: 64/128-bit WEP, WPA/WPA-PSK2

#### Others

- Certification CE, FCC, RoHS
- System Requirements

Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0. or other Java-enabled browser

Package Contents AC750 Wi-Fi Range Extender RE200 Quick Installation Guide

offications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies CO., Ltd. Other brands and product names are trademarks or register imum extended Wil-Fl. coverage peoplication is based on performance test results. Actual Wi-Fl. coverage may vary due to different environment, building material and writer. Districtions. Actual data throughput, and wireless coverage will vary due to network conditions and environmental factors including volume of network track, building materials essentiations or warranties about this product's compatibility with any future standards. 802:1 to 1 500Mbps is approximately 3 times laster than 802.1 to 450Mbps. 2 4GHz Perf

www.tp-link.com

TP-Link AC750 Wi-Fi Range Extender RE200